





## Beauty & Strength

Ambient Series by Safe-Way can add rustic charm, contemporary composition or classic curb appeal to any home or project be it residential, commercial or industrial. The superior thermal performance of Ambient's high density polyurethane foam provides added strength, performance and durability combined with ease of use and low maintenance. The multitude of designs, options and colors of the Ambient Series will offer you endless possibilities to your new home or home improvement upgrade. "Make a Statement" choose American Made and American Owned Safe-Way.

Make a Statement.













## **ESTATE WINDOW SERIES**



Brass Pencil Four Square	Pewter Pencil Four Square	Brass Pencil Six Square	Pewter Pencil Six Square
Brass Pencil Two Diamond	Pewter Pencil Two Diamond		
Model 89, 91, 272 & 273   1	Medium   Raised Panel		

Brass Pencil Four Square Pewter Pencil Four Square

Brass Pencil Six Square



Pewter Pencil Two Diamond

Brass Pencil Two Diamond

Model 84, 86, 87, 88, 92, 93, 94, 95, 272 & 273 | Long Ranch | Raised Panel

	$\diamond \diamond \diamond \diamond = \diamond \diamond \diamond \diamond$	

Brass Pencil Ten Square

Pewter Pencil Ten Square

Brass Pencil Four Diamond Pewter Pencil Four Diamond

\*Safe-Way recommends viewing samples of Gentry style window prior to ordering. Gentry depictions on this literature are actual photography however lighting inside or outside the garage can significantly impact the "look" of these windows. Please consult with your dealer prior to purchase.





## CONSTRUCTION

Two deep-drawn, tension-leveled, galvanized steel skins are polyester painted. The skins encapsulate a high density injected polyurethane core which is bonded using a polyurethane adhesive. Section joints sealed with a polypropylene bulb thermal break anchored within the polyurethane core. This construction method provides superb thermal performance, durability,strength, sound deadening qualities, and dent resistance for an all-around superior product.

(A)

(B)

(C)

(D)

 $\bigcirc$ 

 $(\mathbf{B})$ 

A

- A. Finish Painted Coat
- **B.** Primer Coat
- C. Galvanized Layer
- **D.** Steel

- **A.** Tongue and groove enclosed with bulb type polypropylene thermal break anchored within the polyurethane core.
- **B.** 2" polyurethane injected insulation provides an R-value of 17.68
- C. Steel skins inside and out provide maximum durability.
- **D.** 20 gauge pre-painted heavy steel end stiles for added strength.
- **E.** Interior 20 gauge backer plate full height of section at all hinge points.

\* other features include: 11 ball nylon rollers provide quiet operation and long lasting durability.

Heavy duty galvanized 14 gauge hardware

Aluminum bottom retainer with vinyl weatherstrip.

E.

(C)

Distributed by:



A

(D)

As Safe-Way Door constantly strives to improve our product, all specifications listed in this informative brochure are subject to change without notice or obligation. Printed color may vary from actual color, please check with your local dealer for color swatches. 04/2019



3814 East U.S. 30 Warsaw, IN 46580 574-267-4861 • Fax: 574-267-2871 safe-waydoor.com